

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Issue date: 12/1/2023 Revision date: 12/1/2023 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Name : Crystal air dry clearcoat
Trade name : MEGA CLEAR 8600

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : The product is intended for professional use

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

NOVOL Sp. z o.o. Żabikowska 7/9

62-052 KOMORNIKI - Poland

Poland

T 0048618109800 - F 0048618109809 sekretariat@novol.com - www.novol.com

E-mail address of competent person responsible for the SDS: dokumentacja@novol.com

#### 1.4. Emergency telephone number

Emergency number : 112

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Highly flammable liquid and vapour.

## 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS02

GHS07

Signal word (CLP) : Danger Contains : acetone

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing vapours, spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P312 - Call doctor if you feel unwell.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

#### 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
dioctyltin dilaurate (3648-18-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
dioctyltin dilaurate(3648-18-8)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493- 29	20 – 30	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
methyl acetate substance with national workplace exposure limit(s) (GB)	CAS-No.: 79-20-9 EC-No.: 201-185-2 EC Index-No.: 607-021-00-X REACH-no: 01-2119459211-	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
acetone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	< 8	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9, aromatics	CAS-No.: 128601-23-0 EC-No.: 918-668-5 REACH-no: 01-2119455851- 35	< 2	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 (M=1) EUH066
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	CAS-No.: 104810-48- 2+104810-47-1+ 25322-68-3 EC-No.: 400-830-7 EC Index-No.: 607-176-00-3 REACH-no: 01-2119472279- 28	< 1.5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS-No.: 1065336-91-5 EC-No.: 915-687-0 REACH-no: 01-2119491304- 40	< 0.8	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane	CAS-No.: 77-58-7 EC-No.: 201-039-8 EC Index-No.: 050-030-00-3 REACH-no: 01-2119496068- 27	< 0.27	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360FD STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
dioctyltin dilaurate substance listed as REACH Candidate (Dioctyltin dilaurate, stannane, dioctyl-, bis(coco acyloxy) derivs., and any other stannane, dioctyl-, bis(fatty acyloxy) derivs. wherein C12 is the predominant carbon number of the fatty acyloxy moiety)	CAS-No.: 3648-18-8 EC-No.: 222-883-3 EC Index-No.: 050-031-00-9 REACH-no: 01-2119979527- 19	≤ 0.1	Repr. 1B, H360D STOT RE 1, H372

Full text of H- and EUH-statements: see section 16

## **SECTION 4: First aid measures**

First-aid measures after inhalation

## 4.1. Description of first aid measures

First-aid measures general : General information. Refer to section 11.

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash

immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse

immediately with plenty of water and seek medical advice.

First-aid measures after ingestion : If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Vapours may cause drowsiness and dizziness.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : May cause eye irritation.

12/1/2023 (Revision date) GB - en 3/18

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO2, alcohol-resistant foam or waterspray.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon monoxide. Other toxic gases.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct

or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal

protective equipment as required. See Section 8.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. See Section 8.

## 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

## 6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically

recover the product.

#### 6.4. Reference to other sections

Disposal considerations. See Section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking. Use only outdoors or in a well-

ventilated area. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be

allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

#### 7.3. Specific end use(s)

No additional information available

12/1/2023 (Revision date) GB - en 4/18

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## 8.1.1 National occupational exposure and biological limit values

n-butyl acetate (123-86-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	n-Butyl acetate	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	723 mg/m³	
IOEL STEL [ppm]	150 ppm	
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831	
United Kingdom - Occupational Exposure Limits		
Local name	Butyl acetate	
WEL TWA (OEL TWA) [1]	724 mg/m³	
WEL TWA (OEL TWA) [2]	150 ppm	
WEL STEL (OEL STEL)	966 mg/m³	
WEL STEL (OEL STEL) [ppm]	200 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
acetone (67-64-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Acetone	
IOEL TWA [ppm]	500 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Acetone	
WEL TWA (OEL TWA) [1]	1210 mg/m³	
WEL TWA (OEL TWA) [2]	500 ppm	
WEL STEL (OEL STEL)	3620 mg/m³	
WEL STEL (OEL STEL) [ppm]	1500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
methyl acetate (79-20-9)		
United Kingdom - Occupational Exposure Limits		
Local name	Methyl acetate	
WEL TWA (OEL TWA) [1]	616 mg/m³	
WEL TWA (OEL TWA) [2]	200 ppm	
WEL STEL (OEL STEL)	770 mg/m³	
WEL STEL (OEL STEL) [ppm]	250 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 8.1.2. Recommended monitoring procedures

Monitoring methods	
9	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

## 8.1.3. Air contaminants formed

No additional information available

## 8.1.4. DNEL and PNEC

n-butyl acetate (123-86-4)		
PNEC (Water)		
PNEC aqua (freshwater)	0.18 mg/l	
PNEC aqua (marine water)	0.018 mg/l	
PNEC aqua (intermittent, freshwater)	0.36 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.981 mg/kg dwt	
PNEC sediment (marine water)	0.0981 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.0903 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	35.6 mg/l	
Hydrocarbons, C9, aromatics (128601-23-0)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	25 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	150 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	11 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	32 mg/m³	
Long-term - systemic effects, dermal	11 mg/kg bodyweight/day	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4 (1065336-91-5)	-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.5 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	0.68 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.05 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	0.17 mg/m³	
Long-term - systemic effects, dermal	0.25 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.0022 mg/l	
PNEC aqua (marine water)	0.00022 mg/l	
PNEC aqua (intermittent, freshwater)	0.009 mg/l	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-(1065336-91-5)	-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
PNEC (Sediment)	
PNEC sediment (freshwater)	1.05 mg/kg dwt
PNEC sediment (marine water)	0.11 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.21 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	1 mg/l
dibutyltin dilaurate; dibutyl[bis(dodecanoylox	y)] stannane (77-58-7)
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	2.08 mg/kg bodyweight/day
Acute - systemic effects, inhalation	0.059 mg/m³
Long-term - systemic effects, dermal	0.43 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.02 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	0.5 mg/kg bodyweight/day
Acute - systemic effects, inhalation	0.04 mg/m³
Acute - systemic effects, oral	0.02 mg/kg bodyweight/day
Long-term - systemic effects,oral	0.0031 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.0046 mg/m³
Long-term - systemic effects, dermal	0.16 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.000463 mg/l
PNEC aqua (marine water)	0.0000463 mg/l
PNEC aqua (intermittent, freshwater)	0.00463 mg/l
PNEC aqua (intermittent, marine water)	0.00463 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.05 mg/kg dwt
PNEC sediment (marine water)	0.005 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0407 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0.2 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

## 8.1.5. Control banding

No additional information available

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):







## 8.2.2.1. Eye and face protection

#### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

## 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

## 8.2.2.4. Thermal hazards

No additional information available

## 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Colourless. Odour : characteristic. Odour threshold : No data available Melting point : Not applicable Freezing point : Not available Boiling point : 57 - 126 °C Flammability : Not applicable : No data available. Explosive properties

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Lower explosion limit: 1.2 vol % n-butyl acetateUpper explosion limit: 15 vol % n-butyl acetateFlash point: -13 °C METHYL ACETATE

Auto-ignition temperature : 415 °C

Decomposition temperature : Not available
pH : Not applicable
Viscosity, kinematic : Not available
Solubility : Slightly soluble.
Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : 13 hPa n-butyl acetate

Vapour pressure at  $50^{\circ}$ C: Not availableDensity:  $\approx 1 \text{ g/cm}^3$ Relative density: Not availableRelative vapour density at  $20^{\circ}$ C: Not availableParticle characteristics: Not applicable

## 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions of use.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g, by grounding). Protect from sunlight. Avoid high temperatures.

## 10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon monoxide. Other toxic gases.

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

n-butyl acetate (123-86-4)	
LD50 oral rat	12.2 ml/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 4.9 mg/l Source: ECHA

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hydrocarbons, C9, aromatics (128601	-23-0)
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 6193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
Reaction mass of Bis(1,2,2,6,6-pentar (1065336-91-5)	nethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
LD50 oral rat	3230 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), 95% CL: 2615 - 4247
LD50 dermal rat	> 3170 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
dibutyltin dilaurate; dibutyl[bis(dodec	anoyloxy)] stannane (77-58-7)
LD50 oral rat	2071 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) Remarks on results: other:, 95% CL: 1207 - 5106
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 2000 mg/kg
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
dioctyltin dilaurate (3648-18-8)	
LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rat	≥ 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 2000 mg/kg
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)     pH: Not applicable
n-butyl acetate (123-86-4)	
рН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
n-butyl acetate (123-86-4)	
рН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons, C9, aromatics (128601	1-23-0)
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
dibutyltin dilaurate; dibutyl[bis(doded	canoyloxy)] stannane (77-58-7)
STOT-single exposure	Causes damage to organs.
acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
methyl acetate (79-20-9)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
Hydrocarbons, C9, aromatics (128601	1-23-0)
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity Study in Rodents)
Reaction mass of Bis(1,2,2,6,6-pentar (1065336-91-5)	methyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
NOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))
dibutyltin dilaurate; dibutyl[bis(doded	canoyloxy)] stannane (77-58-7)
STOT-repeated exposure	Causes damage to organs (immune system) through prolonged or repeated exposure.
dioctyltin dilaurate (3648-18-8)	
STOT-repeated exposure	Causes damage to organs (immune system) through prolonged or repeated exposure.
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
n-butyl acetate (123-86-4)	
Viscosity, kinematic	0.83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'
Reaction mass of Bis(1,2,2,6,6-pentar (1065336-91-5)	methyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
Viscosity, kinematic	478 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'
methyl acetate (79-20-9)	
Viscosity, kinematic	0.391 mm²/s
<u> </u>	•

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 11.2. Information on other hazards

No additional information available

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Hazardous to the aquatic environment, short-term

(acute)

: Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term

: Harmful to aquatic life with long lasting effects.

(chronic)

Not rapidly degradable

ot rapidly degradable					
n-butyl acetate (123-86-4)					
LC50 - Fish [1]	18 mg/l Source: ECHA				
EC50 - Crustacea [1]	44 mg/l Source: ECHA				
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina				
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)				
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)				
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'				
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'				
Hydrocarbons, C9, aromatics (128601-23-0)					
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)				
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)				
Reaction mass of Bis(1,2,2,6,6-pentamethyl (1065336-91-5)	-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate				
LC50 - Fish [1]	0.9 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)				
EC50 72h - Algae [1]	1.68 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)				
EC50 72h - Algae [2]	0.42 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)				
dibutyltin dilaurate; dibutyl[bis(dodecanoyl	oxy)] stannane (77-58-7)				
LC50 - Fish [1]	21.2 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)				
EC50 - Crustacea [1]	1.7 – 3.4 mg/l Test organisms (species): Daphnia magna				
EC50 - Crustacea [2]	< 463 μg/l Test organisms (species): Daphnia magna				
EC50 72h - Algae [1]	> 1 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)				
acetone (67-64-1)					
LC50 - Fish [1]	6210 – 8120 mg/l Source: ECHA				
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'				
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'				

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

methyl acetate (79-20-9)	
LC50 - Fish [1] 250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brach	
EC50 - Crustacea [1]	1026.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
dioctyltin dilaurate (3648-18-8)	
LC50 - Fish [1]	> 0.09 mg/l Source: ECHA
EC50 - Crustacea [1]	> 0.21 mg/l Source: ECHA
EC50 72h - Algae [1]	> 0.002 mg/l Source: ECHA

## 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)				
Partition coefficient n-octanol/water (Log Pow)	1.78 Source: HSDB			
dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)				
Partition coefficient n-octanol/water (Log Pow)	4.44 Source: ECHA			
acetone (67-64-1)				
Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC			
methyl acetate (79-20-9)				
Partition coefficient n-octanol/water (Log Pow)	0.18 Source: ICSC			
dioctyltin dilaurate (3648-18-8)				
Partition coefficient n-octanol/water (Log Pow)	9.26 Source: ECHA			

#### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

Component	
dioctyltin dilaurate (3648-18-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Do not discharge into drains.

12/1/2023 (Revision date) GB - en 13/18

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Product/Packaging disposal recommendations

- : This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
- Additional information : Flammable vapours may accumulate in the container.

European List of Waste (LoW, EC 2000/532)

: 08 01 11\* - waste paint and varnish containing organic solvents or other dangerous

substances

15 01 10\* - packaging containing residues of or contaminated by dangerous substances

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA	
14.1. UN number or ID number			
UN 1866	UN 1866	UN 1866	
14.2. UN proper shipping name			
RESIN SOLUTION	RESIN SOLUTION	Resin solution	
Transport document description			
UN 1866 RESIN SOLUTION, 3, II, (D/E)	UN 1866 RESIN SOLUTION, 3, II (-13°C c.c.)	UN 1866 Resin solution, 3, II	
14.3. Transport hazard class(es)			
3	3	3	
3		3	
14.4. Packing group			
П	II	11	
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	
No supplementary information available			

## 14.6. Special precautions for user

## Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 5l
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Transport category (ADR) : 2

Orange plates :

33 1866

Tunnel restriction code (ADR) : D/E EAC code : •3YE

#### Transport by sea

Limited quantities (IMDG) : 5 L
Special packing provisions (IMDG) : PP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : B

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### Air transport

No data available

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

## **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

## **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains substance(s) listed on the REACH Candidate List in concentrations ≥ 0.1 % or SCL: Dioctyltin dilaurate, stannane, dioctyl-, bis(coco acyloxy) derivs., and any other stannane, dioctyl-, bis(fatty acyloxy) derivs. wherein C12 is the predominant carbon number of the fatty acyloxy moiety (EC 222-883-3, CAS 3648-18-8)

#### **PIC Regulation (Prior Informed Consent)**

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): dibutyltin dilaurate (77-58-7), dioctyltin dilaurate (3648-18-8)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

## Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

## **Explosives Precursors Regulation (2019/1148)**

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name		Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-usedhome-made-explosives\_en

#### **Drug Precursors Regulation (273/2004)**

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

#### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## **SECTION 16: Other information**

## Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:				
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways			
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road			
ATE	Acute Toxicity Estimate			
BCF	Bioconcentration factor			
BLV	Biological limit value			
BOD	Biochemical oxygen demand (BOD)			
COD	Chemical oxygen demand (COD)			
DMEL	Derived Minimal Effect level			
DNEL	Derived-No Effect Level			
EC-No.	European Community number			
EC50	Median effective concentration			
EN	European Standard			
IARC	International Agency for Research on Cancer			
IATA	International Air Transport Association			
IMDG	International Maritime Dangerous Goods			
LC50	Median lethal concentration			
LD50	Median lethal dose			
LOAEL	Lowest Observed Adverse Effect Level			
NOAEC	No-Observed Adverse Effect Concentration			
NOAEL	No-Observed Adverse Effect Level			
NOEC	No-Observed Effect Concentration			
OECD	Organisation for Economic Co-operation and Development			
OEL	Occupational Exposure Limit			
PBT	Persistent Bioaccumulative Toxic			
PNEC	Predicted No-Effect Concentration			
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail			
SDS	Safety Data Sheet			
STP	Sewage treatment plant			
ThOD	Theoretical oxygen demand (ThOD)			
TLM	Median Tolerance Limit			
VOC	Volatile Organic Compounds			
CAS-No.	Chemical Abstract Service number			
N.O.S.	Not Otherwise Specified			
vPvB	Very Persistent and Very Bioaccumulative			
ED	Endocrine disrupting properties			

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Data sources : ECHA (European Chemicals Agency).

Training advice : Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUF	I-statements:		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Asp. Tox. 1	Aspiration hazard, Category 1		
EUH066	Repeated exposure may cause skin dryness or cracking.		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H304	May be fatal if swallowed and enters airways.		
H314	Causes severe skin burns and eye damage.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H341	Suspected of causing genetic defects.		
H360D	May damage the unborn child.		
H360FD	May damage fertility. May damage the unborn child.		
H361f	Suspected of damaging fertility.		
H370	Causes damage to organs.		
H372	Causes damage to organs through prolonged or repeated exposure.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Muta. 2	Germ cell mutagenicity, Category 2		
Repr. 1B	Reproductive toxicity, Category 1B		
Repr. 2	Reproductive toxicity, Category 2		
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C		
Skin Sens. 1	Skin sensitisation, Category 1		
Skin Sens. 1A	Skin sensitisation, category 1A		
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1		
STOT SE 1	Specific target organ toxicity – single exposure, Category 1		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:				
Flam. Liq. 2	H225	On basis of test data		
Eye Irrit. 2	H319	Expert judgement		
Skin Sens. 1	H317	Calculation method		
STOT SE 3	H336	Calculation method		
Aquatic Chronic 3	H412	Calculation method		

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.