

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Issue date: 1/4/2010 Revision date: 1/2/2023 Supersedes version of: 2/22/2021 Version: 5.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Name : Moulding compound

Trade name : FILL 4

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : The product is intended for professional use

Repair and maintenance of ships and boats

### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

NOVOL Sp. z o.o. Żabikowska 7/9 62-052 KOMORNIKI

Poland

T 0048618109800 - F 0048618109809

E-mail address of competent person responsible for the SDS: dokumentacja@novol.com

#### 1.4. Emergency telephone number

Emergency number : 112

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225 Skin corrosion/irritation, Category 2 H315 Serious eye damage/eye irritation, Category 2 H319 Skin sensitisation, Category 1 H317 Reproductive toxicity, Category 2 H361d Specific target organ toxicity - Repeated exposure, Category 1 H372

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS07

GHS08

Signal word (CLP) : Danger

styrene, methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate Contains

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

H361d - Suspected of damaging the unborn child.

H372 - Causes damage to organs (hearing organs) through prolonged or repeated

exposure.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P260 - Do not breathe dust, vapours.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P312 - Call doctor if you feel unwell.

#### 2.3. Other hazards

Other hazards which do not result in classification

: Vapour could form explosive mixture with air. Vapours are heavier than air and spread above ground. Hazardous polymerization may occur if exposed to high temperature.

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
styrene substance with national workplace exposure limit(s) (GB) (Note D)	CAS-No.: 100-42-5 EC-No.: 202-851-5 EC Index-No.: 601-026-00-0 REACH-no: 01-2119457861- 32	5 – 15	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT RE 1, H372
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note D)	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6 REACH-no: 01-2119452498- 28	< 7	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335

Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of H- and EUH-statements: see section 16

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general

: General information. Refer to section 11.

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact

: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.

1/2/2023 (Revision date) GB - en 2/12

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse

immediately with plenty of water and seek medical advice.

First-aid measures after ingestion : If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Vapours may cause drowsiness and dizziness.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : May cause eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO2, alcohol-resistant foam or waterspray.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon monoxide. Other toxic gases.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct

or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal

protective equipment as required. See Section 8.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. See Section 8.

### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

#### 6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically

recover the product.

### 6.4. Reference to other sections

Disposal considerations. See Section 13.

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-

ventilated area. Wear personal protective equipment.

1/2/2023 (Revision date) GB - en 3/12

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

### 7.3. Specific end use(s)

No additional information available

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

## 8.1.1 National occupational exposure and biological limit values

styrene (100-42-5)		
United Kingdom - Occupational Exposure Limits		
Local name	Styrene	
WEL TWA (OEL TWA) [1]	430 mg/m³	
WEL TWA (OEL TWA) [2]	100 ppm	
WEL STEL (OEL STEL)	1080 mg/m³	
WEL STEL (OEL STEL) [ppm]	250 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Methyl methacrylate	
IOEL TWA [ppm]	50 ppm	
IOEL STEL [ppm]	100 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU	
United Kingdom - Occupational Exposure Limits		
Local name	Methyl methacrylate	
WEL TWA (OEL TWA) [1]	208 mg/m³	
WEL TWA (OEL TWA) [2]	50 ppm	
WEL STEL (OEL STEL)	416 mg/m³	
WEL STEL (OEL STEL) [ppm]	100 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

### 8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	EN 482. Workplace exposure - General requirements for the performance of procedures
	for the measurement of chemical agents.

### 8.1.3. Air contaminants formed

No additional information available

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 8.1.4. DNEL and PNEC

styrene (100-42-5)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	100 mg/m³	
Acute - local effects, inhalation	100 mg/m³	
Long-term - systemic effects, inhalation	100 mg/m³	
Long-term - local effects, inhalation	100 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	10 mg/m³	
Acute - local effects, inhalation	10 mg/m³	
Long-term - systemic effects,oral	7.7 μg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1 mg/m³	
Long-term - local effects, inhalation	1 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.04 mg/l	
PNEC aqua (marine water)	0.04 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.418 mg/kg dwt	
PNEC sediment (marine water)	0.418 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.146 mg/kg dwt	

## 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

## 8.2.2. Personal protection equipment

### Personal protective equipment symbol(s):







## 8.2.2.1. Eye and face protection

## Eye protection:

Safety glasses

### 8.2.2.2. Skin protection

## Skin and body protection:

Wear suitable protective clothing

## Hand protection:

Protective gloves

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

### 8.2.2.3. Respiratory protection

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

## Environmental exposure controls:

Avoid release to the environment.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Grey.

Odour characteristic. Sweet. Odour threshold 0.43 mg/m3 styrene : Not applicable Melting point Freezing point : Not available : 146 °C Boiling point : Not applicable Flammability Explosive properties : No data available. **Explosive limits** : Not available Lower explosion limit : 1.1 vol % styrene Upper explosion limit : 8 vol % styrene

Flash point : 10 °C Auto-ignition temperature : 400 °C Decomposition temperature : Not available : Not available рΗ Viscosity, kinematic : Not available Viscosity, dynamic : 7200 - 11400 mPa.s Solubility : Slightly soluble. Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : 7.3 hPa styrene Vapour pressure at 50°C : Not available Density : 1.7 – 1.8 g/cm<sup>3</sup> Relative density : Not available : Not available Relative vapour density at 20°C : 3.6 styrene Relative density of saturated gas/air mixture Particle characteristics : Not applicable

#### 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

No additional information available

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 9.2.2. Other safety characteristics

No additional information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions of use.

#### 10.3. Possibility of hazardous reactions

Can react violently with alkalis, as well as a lot of organic products such as alcohols and amines. Hazardous polymerization may occur if exposed to high temperature.

#### 10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g, by grounding). Protect from sunlight. Avoid high temperatures.

### 10.5. Incompatible materials

/ · · · · · · · · · · · ·

No contact with: strong acids, strong bases and strong oxidants.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon monoxide. Other toxic gases.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

styrene (100-42-5)		
LD50 oral rat	5000 mg/kg Source: ECHA	
LD50 dermal rat	> 2000 mg/kg Source: ECHA	
LC50 Inhalation - Rat (Vapours)	11.8 mg/l Source: ECHA	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)		
LD50 oral rat	7900 mg/kg Source: NITE, HSDB, ChemIDplus	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LC50 Inhalation - Rat [ppm]	7093 ppm Source: HSDB	
Skin corrosion/irritation :	Causes skin irritation.	
Serious eye damage/irritation :	Causes serious eye irritation.	

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

styrene (100-42-5)	
IARC group	2B - Possibly carcinogenic to humans

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)		
IARC group	3 - Not classifiable	
Reproductive toxicity	: Suspected of damaging the unborn child.	
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure	: Causes damage to organs (hearing organs) through prolonged or repeated exposure.	
styrene (100-42-5)		
STOT-repeated exposure	Causes damage to organs (hearing organs) through prolonged or repeated exposure.	
spiration hazard	: Not classified (Based on available data, the classification criteria are not met)	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)		
Viscosity, kinematic	0.561 mm²/s	
Viscosity, kinematic	0.561 mm <sup>2</sup> /s	

### 11.2. Information on other hazards

No additional information available

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Hazardous to the aquatic environment, short-term

(acute)

m : Not clas

: Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic)

: Not classified (Based on available data, the classification criteria are not met)

Not rapidly degradable

styrene (100-42-5)		
LC50 - Fish [1]	10 mg/l Source: ECHA	
EC50 - Crustacea [1]	4.7 mg/l Source: ECHA	
EC50 72h - Algae [1]	4.9 mg/l Source: ECHA	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)		
LC50 - Fish [1]	> 79 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 - Crustacea [1]	69 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	> 110 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
LOEC (chronic)	68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	37 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic fish	9.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'	

### 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

styrene (100-42-5)	
Partition coefficient n-octanol/water (Log Pow)	2.95 Source: HSDB,CHemIDplus

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)	
Partition coefficient n-octanol/water (Log Pow)	1.38 Source: HSDB

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Regional legislation (waste)

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

European List of Waste (LoW) code

- Disposal must be done according to official regulations.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Do not discharge into drains.
- : This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
- : Flammable vapours may accumulate in the container.
- : 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous
  - substances

15 01 10\* - packaging containing residues of or contaminated by dangerous substances

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA			
14.1. UN number or ID number					
UN 1866	UN 1866	UN 1866			
14.2. UN proper shipping name					
RESIN SOLUTION	RESIN SOLUTION	Resin solution			
Transport document description					
UN 1866 RESIN SOLUTION, 3, III, (D/E)	UN 1866 RESIN SOLUTION, 3, III (10°C c.c.)	UN 1866 Resin solution, 3, III			
14.3. Transport hazard class(es)					
3	3	3			
3	3	3			
14.4. Packing group					
III	III	III			

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	IATA		
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No		
No supplementary information available				

#### 14.6. Special precautions for user

### **Overland transport**

Classification code (ADR) : F1
Limited quantities (ADR) : 5I
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Tunnel restriction code (ADR) : D/E

Tunnel restriction code (ADR) : D/E EAC code : •3Y

#### Transport by sea

Special provisions (IMDG) : 223, 955
Limited quantities (IMDG) : 5 L
Special packing provisions (IMDG) : PP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A

#### Air transport

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.1.1. EU-Regulations

### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

## POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

## Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other information**

## Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:		
European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
European Agreement concerning the International Carriage of Dangerous Goods by Road		
Acute Toxicity Estimate		
Bioconcentration factor		
Biological limit value		
Biochemical oxygen demand (BOD)		
Chemical oxygen demand (COD)		
Derived Minimal Effect level		
Derived-No Effect Level		
European Community number		
Median effective concentration		
European Standard		
International Agency for Research on Cancer		
International Air Transport Association		
International Maritime Dangerous Goods		
Median lethal concentration		
Median lethal dose		
Lowest Observed Adverse Effect Level		
No-Observed Adverse Effect Concentration		
No-Observed Adverse Effect Level		
No-Observed Effect Concentration		
Organisation for Economic Co-operation and Development		
Occupational Exposure Limit		
Persistent Bioaccumulative Toxic		
Predicted No-Effect Concentration		
Regulations concerning the International Carriage of Dangerous Goods by Rail		
Safety Data Sheet		
Sewage treatment plant		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:		
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Data sources : ECHA (European Chemicals Agency).

Training advice : Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:			
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H335	May cause respiratory irritation.		
H361d	Suspected of damaging the unborn child.		
H372	Causes damage to organs through prolonged or repeated exposure.		
Repr. 2	Reproductive toxicity, Category 2		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
Skin Sens. 1	Skin sensitisation, Category 1		
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:			
Flam. Liq. 2	H225	On basis of test data	
Skin Irrit. 2	H315	Calculation method	
Eye Irrit. 2	H319	Calculation method	
Skin Sens. 1	H317	Calculation method	
Repr. 2	H361d	Expert judgment	
STOT RE 1	H372	Calculation method	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.