

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Issue date: 8/1/2017 Revision date: 1/2/2023 Supersedes version of: 10/7/2019 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier 1 1

1.1. Product identifier	
Product form Name Trade name	: Mixture : Polyester tooling paste : PS-P
1.2. Relevant identified uses of the substan	ce or mixture and uses advised against
1.2.1. Relevant identified uses Use of the substance/mixture	: The product is intended for professional use
1.2.2. Uses advised against	
No additional information available	
1.3. Details of the supplier of the safety dat	a sheet
NOVOL Sp. z o.o. Żabikowska 7/9 62-052 KOMORNIKI Poland T 0048618109800 - F 0048618109809 www.novol.com E-mail address of competent person responsible for	the SDS : <u>dokumentacja@novol.com</u>
1.4. Emergency telephone number	
Emergency number	: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Reproductive toxicity, Category 2	H361d
Specific target organ toxicity – Repeated exposure, Category 1	H372
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)

	GHS02 GHS07 GHS08
Signal word (CLP)	: Danger
Contains	: styrene
Hazard statements (CLP)	: H226 - Flammable liquid and vapour.
	H315 - Causes skin irritation.
	H319 - Causes serious eye irritation.
	H361d - Suspected of damaging the unborn child.
	H372 - Causes damage to organs (hearing organs) through prolonged or repeated
	exposure.

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 - Do not breathe dust, vapours. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P312 - Call doctor if you feel unwell.
2.3. Other hazards	
Other hazards which do not result in classification	: Vapour could form explosive mixture with air. Vapours are heavier than air and spread

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

above ground. Hazardous polymerization may occur if exposed to high temperature.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
styrene substance with national workplace exposure limit(s) (GB) (Note D)	CAS-No.: 100-42-5 EC-No.: 202-851-5 EC Index-No.: 601-026-00-0 REACH-no: 01-2119457861- 32	10 – 15	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT RE 1, H372
Naphtha (petroleum), hydrotreated heavy; contains less than 0,1 % w/w benzene (Einecs No 200-753-7) substance with a Community workplace exposure limit (Note P)	CAS-No.: 64742-48-9 EC-No.: 265-150-3 EC Index-No.: 649-327-00-6 REACH-no: 01-2119486659- 16	< 0.2	Asp. Tox. 1, H304
naphthenic acids, copper salts; copper naphthenate	CAS-No.: 1338-02-9 EC-No.: 215-657-0 EC Index-No.: 029-003-00-5 REACH-no:	< 0.18	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Note D : Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Note P : The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: General information. Refer to section 11.

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	 After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.
First-aid measures after eye contact	 Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.
4.2. Most important symptoms and e	ffects, both acute and delayed
Symptoms/effects after inhalation	: Vapours may cause drowsiness and dizziness.
Symptoms/effects after skin contact	: Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media Unsuitable extinguishing media	Dry chemical, CO2, alcohol-resistant foam or waterspray.Do not use a heavy water stream.		
5.2. Special hazards arising from the substance or mixture			
Hazardous decomposition products in case of fire	: Carbon monoxide. Other toxic gases.		
5.3. Advice for firefighters			
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.		

SECTION 6: Accidental release measures
6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel	
Protective equipment	: Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. See Section 8.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

6.3. Methods and material for containment and cleaning up

For containment

: Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.

6.4. Reference to other sections

Disposal considerations. See Section 13.

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including	g any incompatibilities

Technical measures	:	Ground/bond container and receiving equipment.
Storage conditions	:	Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

styrene (100-42-5)		
United Kingdom - Occupational Exposure Limits		
Local name	Styrene	
WEL TWA (OEL TWA) [1]	430 mg/m ³	
WEL TWA (OEL TWA) [2]	100 ppm	
WEL STEL (OEL STEL)	1080 mg/m ³	
WEL STEL (OEL STEL) [ppm]	250 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.1.2. Recommended monitoring procedures

Monitoring methods	
5	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

styrene (100-42-5)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	100 mg/m ³	
Acute - local effects, inhalation	100 mg/m ³	
Long-term - systemic effects, inhalation	100 mg/m ³	
Long-term - local effects, inhalation	100 mg/m ³	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	10 mg/m ³	
Acute - local effects, inhalation	10 mg/m ³	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

styrene (100-42-5)		
Long-term - systemic effects,oral	7.7 μg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1 mg/m ³	
Long-term - local effects, inhalation	1 mg/m ³	
PNEC (Water)		
PNEC aqua (freshwater)	0.04 mg/l	
PNEC aqua (marine water)	0.04 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.418 mg/kg dwt	
PNEC sediment (marine water)	0.418 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.146 mg/kg dwt	

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: (Read the technical data sheet).
Odour	: characteristic. Sweet.
Odour threshold	: 0.43 mg/m ³ styrene
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 146 °C
Flammability	: Not applicable
Explosive properties	: No data available.
Explosive limits	: Not available
Lower explosion limit	: 1.1 vol % styrene
Upper explosion limit	: 8 vol % styrene
Flash point	: 30 °C
Auto-ignition temperature	: 490 °C
Decomposition temperature	: Not available
рН	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: Not determined
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 7.3 hPa styrene
Vapour pressure at 50°C	: Not available
Density	: 0.8 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Relative density of saturated gas/air mixture	: 3.6 styrene
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

10.3. Possibility of hazardous reactions

Can react violently with alkalis, as well as a lot of organic products such as alcohols and amines. Hazardous polymerization may occur if exposed to high temperature.

10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g, by grounding). Protect from sunlight. Avoid high temperatures.

10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon monoxide. Other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	 Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met)
styrene (100-42-5)	
LD50 oral rat	5000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.8 mg/l Source: ECHA
Naphtha (petroleum), hydrotreated	heavy; contains less than 0,1 % w/w benzene (Einecs No 200-753-7) (64742-48-9)
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
naphthenic acids, copper salts; cop	oper naphthenate (1338-02-9)
LD50 oral rat	300 – 500 mg/kg Source: ECHA
LD50 dermal rat	 > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: other:
LD50 dermal rabbit	> 3160 mg/kg Source: ECHA
Skin corrosion/irritation Serious eye damage/irritation	Causes skin irritation. Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity styrene (100-42-5)	: Not classified (Based on available data, the classification criteria are not met)
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Suspected of damaging the unborn child.
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Causes damage to organs (hearing organs) through prolonged or repeated exposure.
styrene (100-42-5)	
STOT-repeated exposure	Causes damage to organs (hearing organs) through prolonged or repeated exposure.
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Viscosity, kinematic	< 1 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'	
1.2. Information on other hazards		
lo additional information available		
SECTION 12: Ecological information		
2.1. Toxicity		
acute)	 Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) 	
styrene (100-42-5)		
LC50 - Fish [1]	10 mg/l Source: ECHA	
EC50 - Crustacea [1]	4.7 mg/l Source: ECHA	
EC50 72h - Algae [1]	4.9 mg/l Source: ECHA	
Naphtha (petroleum), hydrotreated heavy; c	ontains less than 0,1 % w/w benzene (Einecs No 200-753-7) (64742-48-9)	
LC50 - Fish [1]	2200 mg/l Source: IUCLID	
LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID	
naphthenic acids, copper salts; copper nap	hthenate (1338-02-9)	
LC50 - Fish [1]	≈ 5.62 mg/l Test organisms (species): Pimephales promelas	
EC50 - Crustacea [1]	≈ 20 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	≈ 29.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	≈ 17.7 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [1]	≈ 29.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [2]	≈ 18.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

styrene (100-42-5)			
Partition coefficient n-octanol/water (Log Pow)	tition coefficient n-octanol/water (Log Pow) 2.95 Source: HSDB,CHemIDplus		
Naphtha (petroleum), hydrotreated heavy; contains less than 0,1 % w/w benzene (Einecs No 200-753-7) (64742-48-9)			
Partition coefficient n-octanol/water (Log Pow) 2.1 – 6 Source: IUCLID			
naphthenic acids, copper salts; copper naphthenate (1338-02-9)			
Partition coefficient n-octanol/water (Log Pow)	2.05 – 13.25 Source: ECHA		

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains.
Product/Packaging disposal recommendations	: This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
Additional information	: Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	ΙΑΤΑ
14.1. UN number or ID number		
UN 1866	UN 1866	UN 1866
14.2. UN proper shipping name		
RESIN SOLUTION	RESIN SOLUTION	Resin solution
Transport document description		
UN 1866 RESIN SOLUTION, 3, III, (D/E)	UN 1866 RESIN SOLUTION, 3, III (30°C c.c.)	UN 1866 Resin solution, 3, III
14.3. Transport hazard class(es)		
3	3	3
3		
14.4. Packing group		
Ш	111	III
14.5. Environmental hazards	·	
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		
14.6. Special precautions for user		
Overland transport		
Classification code (ADR)	: F1	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Limited quantities (ADR) Special packing provisions (ADR) Mixed packing provisions (ADR) Transport category (ADR) Special provisions for carriage - Packages (ADR)	:	5l PP1 MP19 3 V12
Tunnel restriction code (ADR) EAC code		D/E •3Y
Transport by sea Special provisions (IMDG) Limited quantities (IMDG) Special packing provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG)	::	223, 955 5 L PP1 F-E S-E A

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 16: Other information

Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:				
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways			
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road			
ATE	Acute Toxicity Estimate			
BCF	Bioconcentration factor			
BLV	Biological limit value			
BOD	Biochemical oxygen demand (BOD)			
COD	Chemical oxygen demand (COD)			
DMEL	Derived Minimal Effect level			
DNEL	Derived-No Effect Level			
EC-No.	European Community number			
EC50	Median effective concentration			
EN	European Standard			
IARC	International Agency for Research on Cancer			
ΙΑΤΑ	International Air Transport Association			
IMDG	International Maritime Dangerous Goods			
LC50	Median lethal concentration			
LD50	Median lethal dose			
LOAEL	Lowest Observed Adverse Effect Level			
NOAEC	No-Observed Adverse Effect Concentration			
NOAEL	No-Observed Adverse Effect Level			
NOEC	No-Observed Effect Concentration			
OECD	Organisation for Economic Co-operation and Development			
OEL	Occupational Exposure Limit			
PBT	Persistent Bioaccumulative Toxic			
PNEC	Predicted No-Effect Concentration			
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail			
SDS	Safety Data Sheet			
STP	Sewage treatment plant			
ThOD	Theoretical oxygen demand (ThOD)			
TLM	Median Tolerance Limit			
VOC	Volatile Organic Compounds			
CAS-No.	Chemical Abstract Service number			
N.O.S.	Not Otherwise Specified			
vPvB	Very Persistent and Very Bioaccumulative			
ED	Endocrine disrupting properties			

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Data sources

Training advice

: ECHA (European Chemicals Agency).

: Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:				
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4			
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4			
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1			
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1			
Asp. Tox. 1	Aspiration hazard, Category 1			
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2			
Flam. Liq. 3	Flammable liquids, Category 3			
H226	Flammable liquid and vapour.			
H302	Harmful if swallowed.			
H304	May be fatal if swallowed and enters airways.			
H315	Causes skin irritation.			
H319	Causes serious eye irritation.			
H332	Harmful if inhaled.			
H361d	Suspected of damaging the unborn child.			
H372	Causes damage to organs through prolonged or repeated exposure.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
Repr. 2	Reproductive toxicity, Category 2			
Skin Irrit. 2	Skin corrosion/irritation, Category 2			
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1			

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Repr. 2	H361d	Expert judgment
STOT RE 1	H372	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.