

## ISOLATOR PRIMER HARDENER

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

ISOLATOR PRIMER HARDENER

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Hardener for primer ISOLATOR PRIMER . For professional use in car refinish.

#### 1.3. Data of the supplier Safety Data Sheet

NOVOL Sp. z o.o.  
Ul. Żabikowska 7/9  
PL 62-052 Komorniki

Tel: +48 61 810-98-00  
Fax: +48 61 810-98-09  
[www.novol.pl](http://www.novol.pl)  
[novol@novol.pl](mailto:novol@novol.pl)

Person responsible for the Safety Data Sheet

[dokumentacja@novol.pl](mailto:dokumentacja@novol.pl)

#### 1.4. Emergency telephone number

+48 61 810-99-09 (from 7.00 to 15.00)

### SECTION 2: HAZARD IDENTIFICATION

#### 2.1. Classification of the substance or mixture

The mixture was classified as dangerous pursuant to current regulations - see section 15. Harmful mixture.

#### Classification 1272/2008/WE:

Irritating effect on skin, category 2 (Skin Irrit.2). Causes skin irritation.

Serious eye damage/eye irritation, Hazard Category 1 (Eye Dam. 1). Causes serious eye damage.

Specific target organ toxicity — Single exposure, Hazard Category 3, Respiratory tract irritation (STOT SE 3). May cause respiratory irritation. Specific target organ toxicity — Single exposure, Hazard Category 3, Narcosis (STOT SE 3). May cause drowsiness or dizziness.

Liquid, flammable substances, category 3 (Flam. Liq. 3). Flammable liquid and vapour.

#### 2.2. Label elements:

Contains:

Butan-1-ol

Pictograms:



Signal word:

Danger.

H226  
H315  
H318  
H335  
H336

Flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing vapours/spray.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312

Call a doctor if you feel unwell.

#### 2.3. Other hazards

No available data.

**ISOLATOR PRIMER HARDENER**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1. Substances**

Not applicable.

**3.2. Mixtures**

**Product identification**

**ISOLATOR PRIMER HARDENER**

<b>Substance name</b>	<b>Identification numbers</b>	<b>Classification and marking</b>	<b>Concentration [wt%]</b>
Butan-1-ol	WE: 200-751-6 CAS: 71-36-3 Index no: 603-004-00-6 Registration no: 01-2119484630-38-XXXX	Classification 1272/2008/WE: Flam. Liq. 3; H226 Acute Tox. 4; H302 STOT SE 3; H335 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336	15-25
1-methoxypropan-2-ol	WE: 203-539-1 CAS: 107-98-2 Index no: 603-064-00-3 Registration no: 01-2119457435-35-XXXX	Classification 1272/2008/WE: Flam. Liq. 3; H226	15-22
Butyl acetate	EC: 204-658-1 CAS: 123-86-4 Index no.: 607-025-00-1 Registration no.: 01-2119485493-29-XXXX	Classification 1272/2008/EC: Flam. Liq. 3; H226; STOT SE 3; H336 EUH066	15-20
poliaminoamide	WE: --- CAS: --- Index no.:--- Registration no.: ---	Classification 1272/2008/WE: Eye Dam. 1; H318	3-7
methyl amyl ketone	WE: 203-767-1 CAS: 110-43-0 Index no.: 606-024-00-3 Registration no.: 01-2119902391-49-XXXX	Classification 1272/2008/WE: Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H302	<12
xylene	EC: 215-535-7 CAS: 1330-20-7 Index no.: 601-022-00-9 Registration no.: 01-2119457861-32-XXXX	Classification 1272/2008/EC: Flam. Liq. 3; H226; Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit.2; H315	<11
2-methoxypropanol	WE: 216-455-5 CAS: 1589-47-5 Index no.: 603-106-00-0 Registration no.:--	Classification 1272/2008/WE: Flam. Liq. 3; H226 Repr. 1B; H360D STOT SE 3; H335 Skin Irrit. 2; H315 Eye Dam. 1; H318	<0.06

Full text of the phrases identifying the types of hazards is provided in section 16.

**SECTION 4: FIRST AID MEASURES**

**4.1. Description of first aid measures:**

General information:

See section 11 of the Safety Data Sheet.

Inhalation:

Take the victim outside into fresh air, ensure quiet surrounding; in case of no breath, apply artificial respiration. Call a doctor.

## ISOLATOR PRIMER HARDENER

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures:

##### Skin:

Take off contaminated clothing. Rinse contaminated skin with plenty of lukewarm water for about 15 minutes. If irritation persists, consult a doctor.

##### Eyes:

Rinse immediately with plenty of lukewarm water for about 15 minutes, avoid strong water jet-risk of cornea damage, consult a doctor.

##### Alimentary tract:

Do not provoke vomiting (choking risk). Rinse mouth with water. If conscious, administer 1-2 glasses of warm water. Call a doctor.

Person giving first aid should wear medical gloves.

#### 4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.

#### 4.3. Indications of any immediate medical attention and special treatment needed

Special measures allowing for specialist and immediate aid should be available in the place of work.

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

Powder, foam resistant to alcohols, carbon dioxide, water mist.

#### 5.2. Special hazards arising from the substance or mixture

Fire may cause generation of carbon dioxide and other toxic gases.

#### 5.3. Advice for firefighters

Fire-fighting teams should wear self-contained breathing apparatus and light protective clothing. Cool adjacent tanks by spraying water at a safe distance.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

For persons not being the members of aid giving staff:

Eliminate sources of ignition. Ensure sufficient ventilation of the room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Personal protection measures - section 8 of the Safety Data Sheet.

For persons giving aid:

Persons giving aid should wear protective clothing made of coated, impregnated fabric, protective gloves (viton), tight protective glasses and breathing apparatus: gas mask with A type absorber.

#### 6.2. Environmental precautions

Prevent leakage to the sewage system, surface waters, underground waters and soil.

#### 6.3. Methods and materials for containment and cleaning up

Stop the leakage (close the liquid inflow, seal), place damaged container in an emergency container, remove the liquid mechanically and place it in an emergency container. In case of large leakage, embank the area. In case of small amounts, collect with the use of a binding agent (e.g. mica, diatomaceous earth, sand).

#### 6.4. Reference to other sections

Personal protection measures - see section 8 of the Safety Data Sheet.

Disposal considerations - see section 13 of the Safety Data Sheet.

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Keep away from heat and fire sources. Prevent leakage to the sewage system, surface waters, underground waters and soil. Use in well ventilated rooms. Do not smoke. Do not inhale fumes. Avoid contact with skin and eyes. Take precaution measures against electrostatic discharge. Use personal protection measures - section 8 of the Safety Data Sheet.

## ISOLATOR PRIMER HARDENER

### SECTION 7: HANDLING AND STORAGE

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly sealed, original containers. Do not store near large amounts of organic peroxides and other strong oxidants. Take precaution measures against electrostatic discharge. Store in cool, well ventilated rooms. Protect from low temperatures, the influence of sunrays and heat sources.

#### 7.3. Special end use(s)

Hardener (component B) for epoxy primer. For professional use in car refinish taking into consideration the information included in subsections 7.1 and 7.2.

### SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

#### 8.1. Control parameters

Butan-1-ol CAS 71-36-3 according to:

- *TRGS 900*: MAK: 100ppm, MAK: 310 mg/m<sup>3</sup>, 1(I),DFG, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: STEL 50ppm, 154 mg/m<sup>3</sup>,Sk

Xylene CAS 1330-20-7 according to:

- *TRGS 900*: MAK: 100ppm, MAK: 440 mg/m<sup>3</sup>, 2(II),DFG, H
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 mg/m<sup>3</sup>, 220mg/m<sup>3</sup>, STEL 100ppm, 441 mg/m<sup>3</sup>, Sk, BMGV

Butyl acetate CAS 123-86-4 according to:

- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 150 ppm, 724 mg/m<sup>3</sup>, STEL 200ppm, 966 mg/m<sup>3</sup>

#### 8.2. Exposure control

Respiratory tract protection:

Gas mask with A type absorber (EN 141).

Hand protection:

Protective gloves PN-EN 374-3 (viton, 0.7 mm thick, penetration time > 480 min, nitrile rubber, 0,4 mm thick, penetration time > 30 min)

Eye protection:

Tight protective glasses.

Skin protection:

Proper protective clothing (coated impregnated fabrics).

Workplace:

Fixed fume extraction and general ventilation.

Environmental exposure control:

Prevent leakage to the sewage system, surface waters, underground waters and soil.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	straw
Odour	characteristic
Odour threshold	0.9 ÷ 9 mg/m <sup>3</sup> (Xylene)
pH	11 (1000g/l w 20°C for poliaminoamide)
Melting/freezing point	not applicable
Boiling point	80°C
Flash point	25°C
Autoignition point	Approx. 340°C
Breakdown point	not specified
Evaporation rate	not specified
Flammability (solid, gas)	not applicable
Explosion limits	% bottom: 1.1 vol% top: 8.0 vol% (xylene)
Vapour pressure	6.6 hPa (20°C)(Butan-1-ol)
Vapour density (with regard to air)	3.66 (butyl acetate)

## ISOLATOR PRIMER HARDENER

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Density	about 0.9 g/cm <sup>3</sup> (20°C)
Solubility (in water)	poor
N-octanol/water division ratio	3.12 ÷ 3,2 (xylene)
Viscosity	10 ÷ 15 mPas
Explosive properties	not applicable
Oxidizing properties	not applicable

#### 9.2 Other informations

No available data.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

The product is not reactive under normal conditions.

#### 10.2. Chemical stability

The product remains stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Carbon monoxide and other toxic gases are generated as a result of thermal decomposition.

#### 10.4. Conditions to avoid

Flammable product. Avoid contact with strongly oxidizing agents, peroxides, strong acids and bases. Avoid generation and accumulation of static electricity. Protect from the influence of sunrays and heat sources.

#### 10.5. Incompatible materials

Avoid contact with large amounts of organic peroxides, strong acids and bases as well as other strong oxidants.

#### 10.6. Hazardous decomposition products

Carbon monoxide and other toxic gases are generated as a result of thermal decomposition.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

No experimental data available on the preparation. Evaluation was performed based on the data on dangerous ingredients included in the preparation.

##### a) Acute toxicity

Xylene	LD <sub>50</sub> (rat, ingestion)	5000 mg/kg
	LC <sub>50</sub> (rat, inhalation)	4550 ppm/4h
Butan-1-ol	LD <sub>50</sub> (rat, ingestion)	790 mg/kg
	LC <sub>50</sub> (rat, inhalation)	800 ppm/4h
Butyl acetate	LD <sub>50</sub> (rat, ingestion)	14000 mg/kg
	LC <sub>50</sub> (rat, inhalation)	9660 mg/m <sup>3</sup> /8h
Methyl amyl ketone	LD <sub>50</sub> (rat, oral)	1.600 mg/kg
	LC <sub>50</sub> (rat, inhalation)	2000-4000 ppm/4h
Butanone	LD <sub>50</sub> (rat, oral)	2737mg/kg
	LC <sub>50</sub> (rat, inhalation)	23500mg/m <sup>3</sup> /8h
2-methoxypropanol	LD <sub>50</sub> (rat, oral)	7200 mg/kg

##### b) Skin corrosion/irritation

Causes skin irritation.

##### c) serious eye damage/irritation

Causes serious eye damage.

##### d) respiratory or skin sensitisation

No available data confirming the hazard class.

**ISOLATOR PRIMER HARDENER**

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

**e) germ cell mutagenicity**

The mixture has not been classified as mutagenic. No available data confirming the hazard class.

**f) carcinogenicity**

The mixture has not been classified as cancerogenic. No available data confirming the hazard class.

**g) reproductive toxicity**

The mixture has not been classified as having any harmful effect on reproduction. No available data confirming the hazard class.

**h) STOT-single exposure**

May cause respiratory irritation. May cause drowsiness or dizziness.

**i) STOT- repeated exposure**

No available data confirming the hazard class.

**j) aspiration hazard**

No available data confirming the hazard class.

**Exposure methods:**

Inhalation: Harmful by inhalation. Irritating to respiratory system.

Skin: Harmful in contact with skin. Irritating to skin.

Eyes: may cause irritation .Risk of serious damage to eyes.

Harmful if swallowed. If swallowed, the substance may cause irritation of the alimentary tract, nausea, vomiting and diarrhoea.

**Poisoning symptoms:**

Headache and vertigo, fatigue, decreased muscle power, drowsiness and, in exceptional instances, loss of consciousness.

Fumes might cause drowsiness and vertigo. Vapours may cause drowsiness and dizziness.

**SECTION 12: ECOLOGICAL INFORMATION**

No experimental data available on the preparation. Evaluation was performed based on the data on dangerous ingredients included in the preparation.

**12.1. Toxicity**

Xylene	Daphnia magna EC50 (48hours.) > 7.4 mg/l Evaluation indicator of acute toxicity for mammals: 3; for fish: 4.1 Number in the catalogue of water hazardous substances: 206 Water hazard class: 2
Butan-1-ol	Evaluation indicator of acute toxicity for mammals 1; for fish: 2.9 Number in the catalogue of water hazardous substances: 39 Water hazard class: 1
Toluene	Daphnia magna /EC50 (48h) 11 mg/l Acute toxicity for fish LC50 13mg/l/9h Number in the catalogue of water hazardous substances: 194 Water hazard class: 2
Butyl acetate	Number in the catalogue of water hazardous substances: 42 Water hazard class: 1
Butanone	Daphnia magna /EC50 (48h) > 100 mg/l
Methyl amyl ketone	Toxicity for fish (Pimephales promeles): LC50 131 mg/l/96h Number in the catalogue of water hazardous substances: 3726 Water hazard class: 1

**2-methoxypropanol**

Daphnia magna /EC50 (48h) 23300 mg/l

**12.2. Persistence and degradability**

No available data.

**12.3. Bioaccumulative potential**

No available data.

**12.4. Mobility in soil**

Product very poorly soluble in water.

## ISOLATOR PRIMER HARDENER

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.5. Results of PBT and vPvB assessment

No available data.

#### 12.6. Other adverse effects

No available data.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

The product must be disposed of in compliance with proper local and statutory regulations with regard to waste - see point 15. The product should be disposed with entities which are authorised to conduct activity in the area of collecting, recycling or utilization of waste.

Product remains:

Do not dispose the product into the sewage system. Do not store with communal waste. Remove the remains of the mixture carefully and harden with the use of the proper A component, (waste) primer included in the set. The hardened product is not harmful waste.

**CAUTION:** harden the remains in small portions and keep them away from flammable products. High amounts of heat are released during chemical reaction!

Contaminated container:

A container containing unhardened remains of the product is harmful waste. Do not store with communal waste. The contaminated container should be disposed with entities which are authorized to collection, recover or disposal.

### SECTION 14: TRANSPORT INFORMATION

	ADR/RID	IMO/IMGD	IATA-DGR
14.1. UN number	1866	1866	1866
14.2. UN proper shipping name		RESIN SOLUTION, flammable	
14.3. Transport hazard class(es)	3	3	3
14.4. Packaging group	III	III	III
14.5. Environmental hazards	none	none	none
14.6. Special precautions for user			
Do not transport together with materials of class 1 (excluding materials of class 1.4S) and some materials of classes 4.1 and 5.2. During transport, avoid direct contact with materials of classes 5.1 and 5.2. Do not use an open flame and do not smoke.			
14.7. Transport in bulk according to Annex II of MARPOL Convention and the IBC Code			
Not applicable.			

### SECTION 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Regulation 2006/1907/WE

CLP - Regulation 1272/2008/WE

#### 15.2. Chemical safety assessment

Not performed

### SECTION 16: OTHER INFORMATION

#### Relevant hazard statements listed in Sections 2 to 15:

Flam.Liq.2/3 Liquid, flammable substances, category 2/3

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

STOT SE 3 Toxic effect on target organs – single exposure, category 3

H335 May cause respiratory irritation.

H336 Might cause drowsiness or or dizziness.

**ISOLATOR PRIMER HARDENER**

**SECTION 16: OTHER INFORMATION**

**Relevant hazard statements listed in Sections 2 to 15:**

Acute Tox. 4. Acute toxicity, category 4  
Acute Tox. 4. Acute toxicity, category 4  
H302 Harmful if swallowed.  
H332 Harmful if inhaled.  
H312 Harmful in contact with skin.  
Repr. 2 Reproductive Toxicity category 2  
H361d Suspected of damaging fertility or the unborn child  
Repr. 1B Reproductive toxicity, category 1B  
H 360 May damage fertility or the unborn child  
STOT RE 2 Toxic effect on target organs – repeated exposure, category 2  
H304 May be fatal if swallowed and enters airways.  
H373 May cause damage to through prolonged or repeated exposure  
Skin Irrit. 2 Caustic/irritating effect on skin, category 2  
H315 Causes skin irritation.  
Eye Dam. 1 Serious eye damage  
H318 Causes serious eye damage.  
Eye Irrit. 2 Serious eye damage/eye irritation, Hazard Category 2  
H319 Causes serious eye irritation.  
EUH066 Repeated exposure may cause skin dryness or cracking.

**Explanation of the abbreviations and acronyms used in the Safety Data Sheet**

**CAS no** – numerical symbol ascribed to a chemical substance by the American organization, Chemical Abstracts Service (CAS).

**EC no.** – a number ascribed to a chemical substance in the European List of Notified Chemical Substances (ELINCS) or a number in the European Inventory of Existing Chemical Substances mention in "No-longer polymers" publication (EINECS)

**MPC** – maximum permissible concentration of health hazardous substances in the work place

**MPIC** – maximum permissible instantaneous concentration

**MPCC** - maximum permissible ceiling concentration

**PCB** - permissible concentration in biological material

**UN number** - four-digit identification number of a substance, preparation or product pursuant to UN model regulations

**ADR** – European agreement on international road transport of hazardous materials

**IMO** – International Marine Organization

**RID** – Regulations for international rail transport of hazardous materials

**IMDG-Code** – International marine code for hazardous materials

**ICAO /IATA** – Technical Instructions for Safe Air Transport of Hazardous Materials

The information is based on our current knowledge. This document shall not constitute warranty for product characteristics. Classification was made by calculation method according to the classification rules contained in Regulation 1272/2008/WE.

**Other sources of information**

**ECHA** European Chemicals Agency

**TOXNET** Toxicology Data Network

**IUCLID** International Uniform Chemical Information Database

Changes: General update

Trainings:

With regard to handling, health and safety while working with hazardous substances and mixtures.

With regard to transport of hazardous goods pursuant to the requirements of ADR regulations.

Issued by: NOVOL Sp. z o.o.