

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Issue date: 4/16/2013 Revision date: 1/2/2023 Supersedes version of: 6/1/2017 Version: 4.00

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

1.1. Product identifier	
Product form Name Trade name	: Mixture : THINNER FOR ACRYLIC AND POLYURETHANE PRODUCTS : THINNER
1.2. Relevant identified uses of the substa	ance or mixture and uses advised against
 1.2.1. Relevant identified uses Use of the substance/mixture 1.2.2. Uses advised against No additional information available 	: The product is intended for professional use
1.3. Details of the supplier of the safety da	ata sheet
NOVOL Sp. z o.o. Żabikowska 7/9 62-052 KOMORNIKI Poland T 0048618109800 - F 0048618109809 <u>www.novol.com</u> E-mail address of competent person responsible for	or the SDS : <u>dokumentacja@novol.com</u>
1.4. Emergency telephone number	
Emergency number	: 112
SECTION 2: Hazards identification	
	•

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]		
Flammable liquids, Category 3	H226	
Acute toxicity (dermal), Category 4	H312	
Acute toxicity (inhalation:dust,mist) Category 4	H332	
Skin corrosion/irritation, Category 2	H315	
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	
Full text of H- and EUH-statements: see section 16		

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling a	according to	Regulation	(FC) No.	1272/2008 [0	I PI
Lubening t	looon annig to	negulation			

Hazard pictograms (CLP)		
	GHS02 GHS07	
Signal word (CLP)	: Warning	
Contains	: xylene	
Hazard statements (CLP)	: H226 - Flammable liquid and vapour.	
	H312+H332 - Harmful in contact with skin or if inhaled.	
	H315 - Causes skin irritation.	
	H336 - May cause drowsiness or dizziness.	
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.	
	No smoking.	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

P261 - Avoid breathing vapours, spray. P271 - Use only outdoors or in a well-ventilated area.

- P280 Wear protective gloves, protective clothing, eye protection, face protection.
- P312 Call doctor if you feel unwell.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32	30 – 55	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
n-butyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493- 29	30 – 50	Flam. Liq. 3, H226 STOT SE 3, H336
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791- 29	10 – 20	Flam. Liq. 3, H226

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: General information. Refer to section 11.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	:	Vapours may cause drowsiness and dizziness.
Symptoms/effects after skin contact	:	Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	:	May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	Dry chemical, CO2, alcohol-resistant foam or waterspray.Do not use a heavy water stream.
5.2. Special hazards arising from the subs	tance or mixture
Hazardous decomposition products in case of fire	: Carbon monoxide. Other toxic gases.
5.3. Advice for firefighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
6.1.1. For non-emergency personnel			
Protective equipment	: Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. See Section 8.		
6.2. Environmental precautions			
Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bedies or			

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

6.3. Methods and material for containment and cleaning up

For containment

: Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.

6.4. Reference to other sections

Disposal considerations. See Section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Technical measures Storage conditions

- : Ground/bond container and receiving equipment.
- : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

xylene (1330-20-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Xylene, mixed isomers, pure	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	442 mg/m ³	
IOEL STEL [ppm]	100 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Xylene	
WEL TWA (OEL TWA) [1]	220 mg/m ³ o-,m-,p- or mixed isomers	
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers	
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers	
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
United Kingdom - Biological limit values		
Local name	Xylene, o-, m-, p- or mixed isomers	
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
n-butyl acetate (123-86-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	n-Butyl acetate	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	723 mg/m ³	
IOEL STEL [ppm]	150 ppm	
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831	
United Kingdom - Occupational Exposure Limits		
Local name	Butyl acetate	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

n-butyl acetate (123-86-4)		
WEL TWA (OEL TWA) [1]	724 mg/m ³	
WEL TWA (OEL TWA) [2]	150 ppm	
WEL STEL (OEL STEL)	966 mg/m ³	
, ,		
WEL STEL (OEL STEL) [ppm]	200 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
2-methoxy-1-methylethyl acetate (108-65-6)		
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylacetate	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	550 mg/m ³	
IOEL STEL [ppm]	100 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	1-Methoxypropyl acetate	
WEL TWA (OEL TWA) [1]	274 mg/m ³	
WEL TWA (OEL TWA) [2]	50 ppm	
WEL STEL (OEL STEL)	548 mg/m ³	
WEL STEL (OEL STEL) [ppm]	100 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.1.2. Recommended monitoring procedures

Monitoring methods	
•	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

xylene (1330-20-7)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	289 mg/m ³	
Acute - local effects, inhalation	289 mg/m ³	
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	77 mg/m ³	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	174 mg/m ³	
Acute - local effects, inhalation	174 mg/m ³	
Long-term - systemic effects,oral	1.6 mg/kg bodyweight/day	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

xylene (1330-20-7)		
Long-term - systemic effects, inhalation	14.8 mg/m ³	
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.327 mg/l	
PNEC aqua (marine water)	0.327 mg/l	
PNEC aqua (intermittent, freshwater)	0.327 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	12.46 mg/kg dwt	
PNEC sediment (marine water)	12.46 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2.31 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	6.58 mg/l	
n-butyl acetate (123-86-4)	·	
PNEC (Water)		
PNEC aqua (freshwater)	0.18 mg/l	
PNEC aqua (marine water)	0.018 mg/l	
PNEC aqua (intermittent, freshwater)	0.36 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.981 mg/kg dwt	
PNEC sediment (marine water)	0.0981 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.0903 mg/kg dwt	
PNEC (STP)	·	
PNEC sewage treatment plant	35.6 mg/l	
2-methoxy-1-methylethyl acetate (108-65-6)	·	
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	550 mg/m ³	
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	275 mg/m ³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	36 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	33 mg/m ³	
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day	
Long-term - local effects, inhalation	33 mg/m ³	
PNEC (Water)		
PNEC aqua (freshwater)	0.635 mg/l	
PNEC aqua (marine water)	0.0635 mg/l	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2-methoxy-1-methylethyl acetate (108-65-6)		
PNEC aqua (intermittent, freshwater)	6.35 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3.29 mg/kg dwt	
PNEC sediment (marine water)	0.329 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.29 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

8.2.2.4. Thermal hazards

No additional information available

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Colour Odour Odour threshold Melting point Freezing point Boiling point Flammability Explosive properties Explosive limits Lower explosion limit Upper explosion limit Flash point Auto-ignition temperature Decomposition temperature pH Viscosity, kinematic Viscosity, dynamic Solubility Partition coefficient n-octanol/water (Log Kow) Vapour pressure Vapour pressure at 50°C	: Liquid : Colourless. : characteristic. : $0.9 - 9 \text{ mg/m^3 Xylene}$: Not applicable : Not available : $126 - 140 \text{ °C}$: Not available : $126 - 140 \text{ °C}$: Not available : Not available : Not available : $1.1 \text{ vol } \% \text{ Xylene}$: $8 \text{ vol } \% \text{ Xylene}$: 24 °C : 270 °C : Not available : Not available : $\approx 1.136 \text{ mm^2/s}$: $\approx 1 \text{ mPa.s}$: Slightly soluble. : Not available : 13 hPa Butyl acetate : Not available
Partition coefficient n-octanol/water (Log Kow) Vapour pressure	: Not available : 13 hPa Butyl acetate
Density Relative density Relative vapour density at 20°C Particle characteristics	 ≈ 0.88 g/cm³ Not available Not available Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g, by grounding). Protect from sunlight. Avoid high temperatures.

10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon monoxide. Other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) Acute toxicity (inhalation)	: Harmful in contact with skin. : Harmful if inhaled.
THINNER	
ATE CLP (dermal)	2000 mg/kg bodyweight
ATE CLP (dust,mist)	2.727 mg/l/4h
xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg rat
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat	27124 mg/l
n-butyl acetate (123-86-4)	
LD50 oral rat	12.2 ml/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 4.9 mg/l Source: ECHA
2-methoxy-1-methylethyl acetate (1	08-65-6)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Causes skin irritation.
n-butyl acetate (123-86-4)	
рН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
n-butyl acetate (123-86-4)	
рН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity Reproductive toxicity STOT-single exposure	 Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

n-butyl acetate (123-86-4)		
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)	
2-methoxy-1-methylethyl acetate (108-65-6)		
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)	
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)	
THINNER		
Viscosity, kinematic	≈ 1.136 mm²/s	
n-butyl acetate (123-86-4)		
Viscosity, kinematic	0.83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'	
•	1	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

	Not classified (Based on available data, the classification criteria are not met)		
acute) Hazardous to the aquatic environment, long-term : Not classified (Based on available data, the classification criteria are not met) chronic) Jot rapidly degradable			
xylene (1330-20-7)			
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)		
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia		
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'		
n-butyl acetate (123-86-4)			
LC50 - Fish [1]	18 mg/l Source: ECHA		
EC50 - Crustacea [1]	44 mg/l Source: ECHA		
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina		
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)		
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
2-methoxy-1-methylethyl acetate (108-65-6)			
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes		
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2-methoxy-1-methylethyl acetate (108-65-6)	
	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1.78 Source: HSDB

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

Regional legislation (waste) Waste treatment methods	 Disposal must be done according to official regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains.
Product/Packaging disposal recommendations	: This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
Additional information	: Flammable vapours may accumulate in the container.
European List of Waste (LoW) code	 07 01 04* - other organic solvents, washing liquids and mother liquors 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA	
--------------------------------------	--

ADR	IMDG	ΙΑΤΑ	
14.1. UN number or ID number			
UN 1263	UN 1263	UN 1263	
14.2. UN proper shipping name			
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint related material	
Transport document description			
UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E)	UN 1263 PAINT RELATED MATERIAL, 3, III (24°C c.c.)	UN 1263 Paint related material, 3, III	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	ΙΑΤΑ	
14.3. Transport hazard class(es)			
3	3	3	
3			
14.4. Packing group		1	
III	111	111	
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	
No supplementary information available			

14.6. Special precautions for user

Overland transport Classification code (ADR) Limited quantities (ADR) Special packing provisions (ADR) Mixed packing provisions (ADR) Transport category (ADR) Special provisions for carriage - Packages (ADR)	: F1 : 5I : PP1 : MP19 : 3 : V12
Tunnel restriction code (ADR) EAC code	: D/E : •3Y
Transport by sea Special provisions (IMDG) Limited quantities (IMDG) Special packing provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG)	: 163, 223, 367, 955 : 5 L : PP1 : F-E : S-E : A

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:	
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources Training advice : ECHA (European Chemicals Agency).

: Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
Acute Tox. 4 (Dermal)	H312	Calculation method
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.