



Technical Data Sheet

SILICONE REMOVER

Universal degreaser

PROPERTIES

- A product designed and dedicated for renovation of classic cars
- Efficiently removes grease and silicone
 - Non-irritating smell



SILICONE REMOVER

Technical Data Sheet
30/09/2013

PROPERTIES

A mixture of strong organic solvents that enables fast and effective cleaning of surfaces of various contaminants, including fats, oils, silicone, etc. The universal degreaser is recommended for use between specific coating stages, e.g. after sanding and blowing off the sand dust from the putty, primer sanding, etc.

APPLICATION:

- Steel
- Aluminium
- Galvanised steel
- Stainless steel
- Old paint coatings
- Acrylic fillers
- Polyester putties

CONTENT OF VOLATILE ORGANIC COMPOUNDS

VOC II/B/a limit	850 g/l
Actual VOC content	750 g/l

DEGREASING METHOD

The surface should be washed 2-3 times (in the case of atomizer max. 2 times). A clean piece of cloth should be used each time. Wait until the remover evaporates completely before applying the the coating.

Note: use on well cured coatings only. Removes one-component coatings.

COLOUR

Colourless

STORAGE CONDITIONS

Store in a cool dry room, away from sources of fire and heat.

Avoid direct exposure to sunlight.

SHELF LIFE

SILICONE REMOVER	24 months/20°C
------------------	----------------

SAFETY

See Safety Data Sheet.

OTHER INFORMATION

The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a trial/test application of the product due to the potential variation of product performance between substrate materials. We may not be held liable for defects if final results were affected by factors beyond our control.