

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
 Name : Anti-corrosion Epoxy Primer  
 Trade name : PROTECT 360 TIX

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Use of the substance/mixture : The product is intended for professional use

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

NOVOL Sp. z o.o.

Żabikowska 7/9

62-052 KOMORNIKI

Poland

T 0048618109800 - F 0048618109809

[www.novol.com](http://www.novol.com)

E-mail address of competent person responsible for the SDS : [dokumentacja@novol.com](mailto:dokumentacja@novol.com)

**1.4. Emergency telephone number**

Emergency number : 112

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412
Full text of H- and EUH-statements: see section 16	

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS05

GHS07

GHS08

Signal word (CLP) :

Danger

Contains :

isobutyl methyl ketone

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.  
 H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H318 - Causes serious eye damage.

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Precautionary statements (CLP)	: H351 - Suspected of causing cancer. H412 - Harmful to aquatic life with long lasting effects. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing vapours, spray. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call doctor if you feel unwell.
EUH-statements	: EUH205 - Contains epoxy constituents. May produce an allergic reaction. EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ )	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619-26	< 24	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	< 20	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] substance with national workplace exposure limit(s) (GB) (Note V)(Note W)(Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379-17	< 13	Carc. 2, H351
isobutyl methyl ketone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-10-1 EC-No.: 203-550-1 EC Index-No.: 606-004-00-4 REACH-no: 01-2119473980-30	< 9	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336
butan-1-ol; n-butanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 71-36-3 EC-No.: 200-751-6 EC Index-No.: 603-004-00-6 REACH-no: 01-2119484630-38	< 6	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619-26	( 5 $\leq$ C $\leq$ 100) Eye Irrit. 2, H319 ( 5 $\leq$ C $\leq$ 100) Skin Irrit. 2, H315

Note 10 : The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu$ m.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note V : If the substance is to be placed on the market as fibres (with diameter  $<$  3  $\mu$ m, length  $>$  5  $\mu$ m and aspect ratio  $\geq$  3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

Note W : It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: General information. Refer to section 11.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Vapours may cause drowsiness and dizziness.
Symptoms/effects after skin contact	: Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: May cause eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical, CO <sub>2</sub> , alcohol-resistant foam or waterspray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Carbon monoxide. Other toxic gases.
--	---------------------------------------

### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment : Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. See Section 8.

#### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

#### 6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.

#### 6.4. Reference to other sections

Disposal considerations. See Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.  
Storage temperature : 5 – 35 °C

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Remark	Skin

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>xylene (1330-20-7)</b>	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>butan-1-ol; n-butanol (71-36-3)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butan-1-ol
WEL STEL (OEL STEL)	154 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	50 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>isobutyl methyl ketone (108-10-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	4-Methylpentan-2-one
IOEL TWA [ppm]	20 ppm
IOEL STEL	208 mg/m <sup>3</sup>
IOEL STEL [ppm]	50 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	4-Methylpentan-2-one
WEL TWA (OEL TWA) [1]	208 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	416 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>isobutyl methyl ketone (108-10-1)</b>	
<b>United Kingdom - Biological limit values</b>	
Local name	4-methylpentan-2-one
BMGV	20 µmol/l Parameter: 4-methylpentan-2-one - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	4 mg/m <sup>3</sup> respirable 10 mg/m <sup>3</sup> total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

<b>Monitoring methods</b>	
Monitoring methods	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>xylene (1330-20-7)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	289 mg/m <sup>3</sup>
Acute - local effects, inhalation	289 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	77 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	174 mg/m <sup>3</sup>
Acute - local effects, inhalation	174 mg/m <sup>3</sup>
Long-term - systemic effects, oral	1.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.8 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	12.46 mg/kg dwt
PNEC sediment (marine water)	12.46 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2.31 mg/kg dwt

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>xylene (1330-20-7)</b>	
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	6.58 mg/l
<b>butan-1-ol; n-butanol (71-36-3)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - local effects, inhalation	310 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	3.125 mg/kg bodyweight/day
Long-term - local effects, inhalation	55 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.082 mg/l
PNEC aqua (marine water)	0.0082 mg/l
PNEC aqua (intermittent, freshwater)	2.25 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.178 mg/kg dwt
PNEC sediment (marine water)	0.0178 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.015 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	2476 mg/l
<b>isobutyl methyl ketone (108-10-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	208 mg/m <sup>3</sup>
Acute - local effects, inhalation	208 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11.8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	83 mg/m <sup>3</sup>
Long-term - local effects, inhalation	83 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	155.2 mg/m <sup>3</sup>
Acute - local effects, inhalation	155.2 mg/m <sup>3</sup>
Long-term - systemic effects, oral	4.2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.7 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	4.2 mg/kg bodyweight/day
Long-term - local effects, inhalation	14.7 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.6 mg/l
PNEC aqua (marine water)	0.06 mg/l
PNEC aqua (intermittent, freshwater)	1.5 mg/l

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

isobutyl methyl ketone (108-10-1)	
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	8.27 mg/kg dwt
PNEC sediment (marine water)	0.83 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	1.3 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	27.5 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

#### 8.2.2.4. Thermal hazards

No additional information available



# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow.
Odour	: characteristic.
Odour threshold	: 0.9 – 9 mg/m <sup>3</sup> Xylene
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 114 – 143 °C
Flammability	: Not applicable
Explosive properties	: No data available.
Explosive limits	: Not available
Lower explosion limit	: 1.1 vol % Xylene
Upper explosion limit	: 8 vol % Xylene
Flash point	: 14 °C
Auto-ignition temperature	: 440 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 400 – 2000 mPa.s
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 9 hPa
Vapour pressure at 50°C	: Not available
Density	: 1.5 g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g. by grounding). Protect from sunlight. Avoid high temperatures.

### 10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon monoxide. Other toxic gases.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

<b>xylene (1330-20-7)</b>	
LD50 oral rat	3523 mg/kg rat
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat	27124 mg/l

<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <math>\leq</math> 700) (25068-38-6)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg Source: CHEMIDPLUS

<b>butan-1-ol; n-butanol (71-36-3)</b>	
LD50 oral rat	2292 mg/kg Source: ECHA
LD50 dermal rabbit	3430 mg/kg Source: ECHA

<b>isobutyl methyl ketone (108-10-1)</b>	
LD50 oral rat	2080 mg/kg Source: ECHA
LD50 dermal rabbit	$\geq$ 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.6 mg/l Source: ECHA

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <math>\leq</math> 10 <math>\mu</math>m] (13463-67-7)</b>	
LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l Source: ECHA

Skin corrosion/irritation : Causes skin irritation.

<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <math>\leq</math> 700) (25068-38-6)</b>	
pH	4.5 – 4.7

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <math>\leq</math> 10 <math>\mu</math>m] (13463-67-7)</b>	
pH	7 Source: ECHA

Serious eye damage/irritation : Causes serious eye damage.

<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <math>\leq</math> 700) (25068-38-6)</b>	
pH	4.5 – 4.7

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <math>\leq</math> 10 <math>\mu</math>m] (13463-67-7)</b>	
pH	7 Source: ECHA

Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)  
Carcinogenicity : Suspected of causing cancer.

<b>isobutyl methyl ketone (108-10-1)</b>	
IARC group	2B - Possibly carcinogenic to humans

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] (13463-67-7)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

### butan-1-ol; n-butanol (71-36-3)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

### isobutyl methyl ketone (108-10-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

### xylene (1330-20-7)

LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
----------------------------	---

### butan-1-ol; n-butanol (71-36-3)

LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat
----------------------------	----------------------------------

NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat
----------------------------	----------------------------------

### isobutyl methyl ketone (108-10-1)

LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	--

NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	---

NOAEC (inhalation, rat, vapour, 90 days)	4106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
--	---

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

### butan-1-ol; n-butanol (71-36-3)

Viscosity, kinematic	3.641 mm <sup>2</sup> /s
----------------------	--------------------------

## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Not rapidly degradable

### xylene (1330-20-7)

LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
-----------------	---

EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
----------------------	---

NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
-------------------	--

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <math>\leq</math> 700) (25068-38-6)</b>	
LC50 - Fish [1]	1.41 mg/l Source: National Institute of Technology and Evaluation
EC50 - Crustacea [1]	$\approx$ 2 mg/l Test organisms (species): Daphnia magna
<b>butan-1-ol; n-butanol (71-36-3)</b>	
LC50 - Fish [1]	1376 mg/l Source: ECHA
EC50 - Crustacea [1]	1983 mg/l Source: ECHA
EC50 96h - Algae [1]	225 mg/l Source: ECHA
NOEC (chronic)	4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>isobutyl methyl ketone (108-10-1)</b>	
LC50 - Fish [1]	> 179 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna
<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <math>\leq</math> 10 <math>\mu</math>m] (13463-67-7)</b>	
LC50 - Fish [1]	> 100 mg/l
EC50 72h - Algae [1]	> 50 mg/l Source: ECHA

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <math>\leq</math> 700) (25068-38-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.821 Source: National Institute of Technology and Evaluation
<b>butan-1-ol; n-butanol (71-36-3)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.9 Source: HSDB
<b>isobutyl methyl ketone (108-10-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.31 Source: ChemIDPlus

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains.

# PROTECT 360 TIX




## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Product/Packaging disposal recommendations	: This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
Additional information	: Flammable vapours may accumulate in the container.
European List of Waste (LoW) code	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
<b>14.1. UN number or ID number</b>		
UN 1263	UN 1263	UN 1263
<b>14.2. UN proper shipping name</b>		
PAINT	PAINT	Paint
<b>Transport document description</b>		
UN 1263 PAINT, 3, II, (D/E)	UN 1263 PAINT, 3, II (14°C c.c.)	UN 1263 Paint, 3, II
<b>14.3. Transport hazard class(es)</b>		
3	3	3
		
<b>14.4. Packing group</b>		
II	II	II
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Transport category (ADR)	: 2

Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

#### Transport by sea

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Special packing provisions (IMDG)	: PP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

#### Air transport

No data available

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>Abbreviations and acronyms:</b>	
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources

: ECHA (European Chemicals Agency).

Training advice

: Handle in accordance with good industrial hygiene and safety procedures.

<b>Full text of H- and EUH-statements:</b>	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Carc. 2	Carcinogenicity, Category 2
EUH205	Contains epoxy constituents. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1

# PROTECT 360 TIX

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 2	H225	On basis of test data
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.