



Technical Data Sheet

Date of issue: 07/05/2021

Date of update: 07/05/2021

Version: 1

PLUS PROTECTIVE FILM

P/N: 91314 (300009667) 4 x 5 m

P/N: 39388 (300007518) 4 x 7 m

Product overview:

Thick HDPE plastic film for the masking and protection of surfaces against overspray, dust and moisture. The product is highly resistant to tearing, cracking and stretching. It is available in two sizes, as a 4 x 5 m sheet and a 4 x 7 m sheet. The product is intended for processing with water-borne and solvent coating products.

Characteristics:

- Helps mask and protect car body parts against overspray and other contaminants;
- Resists spray booth temperatures;
- Universal use, including industrial, construction and DIY applications;
- The large sheet size aids in the protection of large areas;
- High mechanical strength;
- Only requires one person to apply.

Technical data:

	Value
Material:	HDPE (high-density polyethylene)
Density:	0.95-0.97 g/cm ³ (DIN-EN 1183)
Film thickness:	6 µm
Packaging format:	Single-unit plastic bag
Quantity in bulk packaging:	40 pcs. (4 x 5 m) or 30 pcs. (4 x 7 m)
Size:	4 x 5 m or 4 x 7 m

Shelf life, storage and application requirements:

The masking film sheet will retain its best performance for 24 months from the production date. Keep at a temperature between 10°C and 30°C. Protect against freezing and UV light. Apply on dry car body panels; if left on a wet coat for a long time the evaporation of water may result in marks from the HDPE film on the car body.

Notice:

The effectiveness of our systems results from laboratory research and many years of experience. The data contained here meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to perform a test application of the product due to its potentially different reaction with different materials. We cannot be held liable for defects if the final results were affected by factors beyond our control. NOVOL reserves the right to improve the product and modify the technical requirements, which may entail modification of the specification. This product is not hazardous if used as intended.

NOVOL Sp. z o.o., ul. Żabikowska 7/9, PL62-052 Komorniki, tel. +48 61 810 98 00, novol.com