



Technical Data Sheet

Date of issue: 10/02/2017,
Date of update: 30/04/2021
Version: 2

SPRAY BOOTH PROTECT

P/N: 90541 (300007943)

Product overview:

A transparent liquid formula that protects the spray booth walls from overspray and deposits. Once applied by spraying, the product forms a slightly tacky film which attracts spray paint mist and dust. The product is applied in 2 or 3 layers with a 2.5 mm nozzle spray gun, an undercoating spray gun, a brush, or a velour roller. Once the adhesive effect is lost, remove the film with a sponge and water. The product helps to reduce swirling dust particles in spray booths, minimising the risk of inclusions and imperfections on spray-coated workpieces.

Characteristics:

- Helps to keep the booth walls clean without the need for labour-intensive cleaning with paint removers;
- The special tacky formula traps spray paint, dust, particles, and dirt on the film surface;
- Ready for application;
- High yield with a long adhesive action life;
- Environmentally friendly and biodegradable;
- Does not change the light colour if applied on lamps.

Technical data:

	Value
Average yield:	8 m ² /l/layer
Capacity:	5 l
Adhesive life after the application:	6 to 8 weeks, depending on the ambient temperature and humidity
Number of layers:	2–3, time to recoating: 20 minutes
Application methods:	Undercoating spray guns, 1.8–2.5 mm nozzle spray guns at 2–3 bar and 125 µm of layer thickness, velour rollers, or brushes
pH:	8–9
Specific gravity:	1.06 g/cm ³

Shelf life; storage and application requirements:

The product will perform best for 24 months from the production date if stored between 5°C and 35°C. Protect from freezing. Store in a cool, dry room, away from sources of fire and heat, avoid exposure to sunlight.

If the spray booth is used often (> 5 times a day), apply another layer on the existing one. If the film loses tackiness, remove with water and recoat with new layers. Do not use below 5°C. If the average temperature in the spray booth remains over 65°C, the product will dry out and lose adhesion faster.

Notice:

The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to perform a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final results were affected by factors beyond our control. NOVOL reserves the right to improve the product and modify the technical requirements, which may entail modification of the specification. This product is not hazardous if used as intended.