



KLARLACK SPRAY

Clearcoat

Description: A fast-dry acrylic resin clearcoat with very good flowability and polishability. Perfect for spot repairs.

Substrates: Thinner-based and water-borne basecoats

VOC content:

VOC II/B/e limit = 840 g/l
Actual VOC content = 690 g/l

Procedure:

Apply two wet layers, leave each to flash off for 5 – 10 minutes at 20°C. The flash-off time depends on the temperature and the layer thickness.



Shake the spray can for about 2 minutes before use for a uniform finish.



Apply 2 to 3 layers on a properly prepared and degreased substrate. Wait until the previous coat is completely matt before applying the next layer.



The hardening time is 2 hours at 20°C.



CAUTION!
Clean the valve after use. To do this, turn the can upside down and spray for approx. 5 seconds until the valve is clear.

Colour: Transparent.

Storage conditions and shelf life:

Store in a dry and cool room, away from sources of fire and heat. Avoid direct exposure to sunlight.
KLARLACK SPRAY: 5 years at 20°C.

Safety regulations: See the product Safety Data Sheet.

Other information:

Index number: 000024104.

The effectiveness of our systems results from laboratory research and many years of experience. The data contained here meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to perform a test application of the product due to potential reactions with different materials. We may not be held liable for defects if the final results were affected by factors beyond our control.